

MAXHUB XBar V50 Kit Datasheet

The MAXHUB XBar V50 is an all-in-one Android-based videobar designed for premium small to medium meeting rooms. Equipped with a 100MP dual-camera system and studio-grade dual speakers, it delivers exceptional audiovisual performance. Enhanced by AI noise reduction, the built-in 12-microphone array ensures crystal-clear audio experience. It can eliminate background interference like keyboard clicks or air conditioning.

Featuring a dedicated AI chipset, the XBar V50 supports advanced functionalities including Auto Framing, Speaker Tracking, Intelligent Focus and Smart Gathering. Its plug-and-play deployment simplifies installation and remote maintenance, while design for Microsoft Device Ecosystem Platform (MDEP) ensures seamless integration.

 Built on
Microsoft Device Ecosystem Platform



100MP Camera System

Ultra-high-resolution camera system redefines image clarity and spatial adaptability



Dual-Lens Camera

Ultra-wide 125° HFOV
Provides a wide range of view in the room



AI-Powered Technology

Auto Framing
Speaker Tracking
Smart Gathering
Intelligent Focus



AI Noise Reduction

Built-in 12 MEMS microphone array with AI noise reduction



Studio-Grade Dual Speakers

Dual 15W
Stereo Sound
Full Frequency



Cloud Device Management

Remotely monitor device status through cloud-based service (MAXHUB Pivot) via an internet connection

Package Contents

| | |
|--------------------------------------|-----|
| XBar V50 (With Standard Accessories) | * 1 |
| Panel AP30 (With Accessories) | * 1 |

| Physical Specification | |
|---------------------------|--|
| Package Dimension (L×W×H) | 770 × 257 × 275 mm / 30.3 × 10.1 × 10.8 in |
| Gross Weight | 9.98 kg / 22.0 lb |
| Content Sharing | |
| Teams (In Meeting) | 1080p@30 |
| Local Sharing (Type-C) | 4K@30 |
| Local Sharing (HDMI) | 4K@30 |

| Device Management | |
|-------------------------|---|
| Control and Management | Microsoft Device Management Platform (Microsoft Teams Admin Center/Intune/ Pro management portal) MAXHUB Pivot |
| Environmental Condition | |
| Operating Temperature | 0°C ~ 40°C / 0°F ~ 104°F |
| Storage Temperature | -20°C ~ 60°C / -4°F ~ 140°F |
| Operating Humidity | 10% ~ 90% RH |
| Storage Humidity | 10%~ 90% RH |
| Altitude | Below 5000 m |

XBar V50:

| Camera | |
|--------------------------|--|
| Camera Quantity | 2 |
| Pixel | 50MP × 2 |
| Sensor | 1/1.55 inch |
| Aperture | F/2.4 |
| Resolution & Frame Rate: | |
| H.264 / MJPEG | 3840 × 2160, 2560 × 1440, 1920 × 1080, 1280 × 720, 1024 × 576, 960 × 540, 800 × 600, 640 × 360. |
| YUY2 | 1920 × 1080, 1280 × 720, 640 × 360 |
| ZOOM | 6x Digital Zoom |
| Field of View | 130° (D), 125° (H), 50° (V) |
| Privacy Shutter | Electric and automatical lens shutter |
| AI Feature | Auto Framing Speaker Tracking Intelligent Focus Smart Gathering Video Fence Audio Fence |
| Operating System | |
| MDEP | Supported |
| OS | Andriod 13 |

| Network | |
|----------------|------------------------------|
| Wi-Fi | Wi-Fi 6, 2×2 MIMO |
| Wi-Fi Protocol | 802.11 a/ b/ g/ n/ ac/ ax |
| Working Band | 2.4 GHz + 5 GHz |
| Bluetooth | 5.2 + BLE |
| Network | 1000 Mbps |

| Power | |
|---------------|---|
| Power Adapter | AC 100-240 V Input and DC 19V/4.5A Output |

| Physical Specification | |
|---------------------------|--|
| Product Dimension (L×W×H) | 650.8 × 76.6 × 95.7 mm / 25.6 × 3.01 × 3.77 in |
| Package Dimension (L×W×H) | 750 × 136 × 246 mm / 29.5 × 5.4 × 9.7 in |
| Net Weight | 2.8 kg / 6.17 lb |
| Gross Weight | 6.0 kg / 13.23 lb |

| Audio | |
|-----------------------|--|
| Speaker: | |
| Speaker Quantity | 2 |
| Sound Channel | 2.0 |
| Total Power (Max.) | 15W + 15W |
| Sound Pressure (Max.) | 83 dB SPL@1W/1M |
| Frequency Range | 80 Hz ~ 20 KHz |
| Microphone: | |
| Microphone Quantity | 12-mic array |
| Pickup Range | 8 m |
| Frequency Range | 20 Hz ~ 16 KHz |
| Sensitivity | -36 ± 1 dBFS |
| Sampling | 48 KHz |
| Expansion | Supports 2 expansion microphones |
| AI Feature | Noise Reduction Echo Cancellation Anti-Reverberation AGC Algorithm Full-duplex |

| Input/Output Port | |
|---------------------|------------------------------|
| USB 3.0 Type-B × 1 | To connect to your PC |
| USB 2.0 Type-A × 1 | For debug and update |
| HDMI Out × 2 | Up to 4K@60Hz, CEC supported |
| HDMI In × 1 | Up to 4K@60Hz |
| Audio In × 1 | For third-party audio input |
| Audio Out × 1 | For third-party audio output |
| RJ45 (Internet) × 1 | For internet connection |
| RJ45 (M Link) × 1 | To connect expansion device |
| DC In × 1 | For 19V power supply |

| Standard Accessories | |
|-----------------------------------|-----|
| Power Adapter | × 1 |
| AC Cable (1.5 m / 4.9 ft) | × 1 |
| HDMI Cable (3 m / 9.8 ft) | × 2 |
| Ethernet Cable (3 m / 9.8 ft) | × 1 |
| Mounted Components (ADA Standard) | × 1 |

Panel AP30:

| Display | |
|------------------------|------------------------------------|
| Size | 11.6 inch |
| Resolution | 1920 × 1080 |
| Frequency Refresh Rate | 60 Hz |
| Backlight Unit | ELED |
| Brightness With Glass | 250 nits (Min.) 300 nits (Max.) |
| Life Time | ≥ 20000 hours |

| Input/Output Port | |
|-----------------------------------|-----|
| RJ45 (INTERNET) | × 1 |
| RJ45 (EXT) | × 1 |
| DC In | × 1 |
| Type-C (INGEST) | × 1 |
| USB 2.0 (Pairing Wireless Dongle) | × 1 |

| Power | |
|--------------|----------------------|
| Power Input | 19V DC 4.5A |
| Power Output | Type-C PD 65W (Max.) |

| Operating System | |
|------------------|------------|
| MDEP | Supported |
| OS | Andriod 13 |

| Touch System | |
|-------------------|------------------------------|
| Type | Capacitive touch |
| Surface Treatment | Anti-fingerprint, Anti-glare |

| Accessories | |
|-----------------------------------|-----|
| Type-C Cable (1.5 m / 4.92 ft) | × 1 |
| Ethernet Cable (7.5 m / 24.61 ft) | × 1 |
| Screwdriver | × 1 |
| Power Adapter | × 1 |
| AC Cable (1.5 m / 4.9 ft) | × 1 |

| Sensor | |
|---------------|----------------------------------|
| Motion Sensor | PIR sensor for automatic wake-up |

| Physical Specification | |
|---------------------------|--|
| Product Dimension (L×W×H) | 278 × 164 × 82 mm / 11 × 6.4 × 3.2 inch |
| Product Weight | 116 kg / 2.56 lb |
| Package Dimension (L×W×H) | 1 pcs: 570 × 246 × 101 mm 4 pcs: 590 × 440 × 280 mm |
| Package Weight | 1 pcs: 3.12 kg |

Statement

Size and weight vary by configuration and manufacturing process, please refer to the actual product. The product images are for illustrative purposes only and may slightly differ in appearance, colour, size, etc. from the actual product. The description, illustrations, etc. in this document may subject to change in accordance with the latest product specification and performance. Should the above-mentioned change in the document become necessary, the document may be updated without written notice.