

EB-PU2220B



The EB-PU2220B is the world's smallest 20,000lm projector¹.

The EB-PU2220B offers users significant advantages including much reduced size and weight, easier installation and set-up, simplified maintenance and great image quality. This ultra-lightweight, compact laser projector has been designed for use in large auditoriums, live events, concerts, conference rooms where it delivers high-impact immersive experiences.

Compact and lightweight

The EB-PU2220B is around 60% smaller and 50% lighter than its predecessor, the EB-L20000U. The reduced weight and size means the projector is easier to store, transport and install, saving on warehouse space as well as labour and delivery costs.

Outstanding image quality

This high lumens, 3LCD projector offers WUXGA resolution with 4K enhancement and HDR for rich textures and sharper images.


Flexibility

The EB-PU2220B enables simple installation, stacking, lens flexibility and control. It includes in-built processing for PC-free stacking which means two supported projectors can be stacked to double the brightness without the need for external computerware.

Reliability

Includes outstanding dust resistance as the hermetically sealed optical engine, and laser light source unit, ensure stable brightness output over long periods, even in high dust environments.

DATASHEET



KEY FEATURES

- **Ultra-lightweight and compact**
The world's smallest 20,000lm projector¹
- **Stunning image displays**
20,000lm, 4K Enhancement technology, WUXGA resolution
- **Easy to use**
Simple installation, stacking, lens flexibility and control
- **Fit-and-forget reliability**
Enhanced dust resistant construction - IP5X certified
- **Environmental benefits**
Lower power consumption, reduced packaging, reduced weight

PRODUCT SPECIFICATIONS

TECHNOLOGY

Projection System	3LCD Technology
LCD Panel	1.03 inch with C2 Fine

IMAGE

Color Light Output	20,000 Lumen- 14,000 Lumen (economy) In accordance with IDMS15.4
White Light Output	20,000 Lumen - 14,000 Lumen (economy) In accordance with ISO 21118:2020
Resolution	WUXGA
Resolution Enhancement	4K enhancement
Aspect Ratio	16:10
On-Screen Pixel Count	4,608,000 (1920x1200 x2)
Contrast Ratio	Over 5,000,000 : 1
Native Contrast	2,000 : 1
Light source	Laser
Laser Light source	20,000 hours Durability High, 30,000 hours Durability Eco
Colour Video Processing	10 Bits
Colour Reproduction	Upto 1.07 billion colours
HDR support	HDR10, HLG

OPTICAL

Throw Ratio	0.35 - 7.41:1, Varies by lens
Zoom	Motorized, Factor:1 - 1.6, Varies by lens
Lens	Varies by lens
Lens Shift	Motorized - Vertical ± 60 %, horizontal ± 18 %, Varies by lens
Lens position memory	10 positions
Screen Size	60 inches - 1,000 inches, Varies by lens
Projection Distance Wide	Varies by lens
Projection Distance Tele	Varies by lens
Projection Lens F Number	Varies by lens
Projection Lens Focal Length	Varies by lens
Projection Lens Focus	Motorized
Interchangeable Lens	Yes
Standard Lens	Not included
Mechanical shutter	Yes

CONNECTIVITY

Interfaces	USB 2.0-A (2x), USB 2.0 Type B (Service Only), RS-232C, Ethernet Interface (1000 Base-T/ 100-Base TX/ 10-Base-T), VGA in, DVI in, HDMI in, HDBaseT, Jack plug out, 3G-SDI Input, 3G-SDI Output, Wireless LAN IEEE 802.11a/b/g/n (optional), Near Field Communication (NFC), USB content playback, Remote
Network Protocol	HTTPS, IPv6, SNMP, ESC/VP.net, PJLink

ADVANCED FEATURES

Security	Kensington lock, Security bar, Password lock, Wireless LAN unit lock, Wireless LAN security, Password protection
Other features	21:9 aspect ratio support, 4K enhancement, Auto Power On, Auto source search, Direct Power on/off, Edge Blending, Freeze image, Horizontal and vertical keystone correction, Lens position memory, Long light source life, OSD copy function, Point correction, Power on button, Quick Corner, Schedule Function, Split-Screen-Function, Super resolution, Web Control, Web Remote, iProjection App
Video Color Modes	Cinema, Dynamic, Natural, Presentation, DICOM SIM, Multi Projection, BT709
Projector control	via: AMX, Crestron, Extron
Sealed Light Source Module	Yes, IP5X rated
Sealed Optical Engine	Yes, IP5X rated

EB-PU2220B

WHAT'S IN THE BOX

- Power cable
- Remote control incl. batteries
- Cable cover
- Lens connector cap
- Document Pack
- Information sheet
- Main unit
- Quick Start Guide

PRODUCT SPECIFICATIONS

GENERAL	
Power consumption	1,143 Watt (Normal On-Mode), 1,301 Watt (Normal Peak-mode), 899 Watt (Eco Peak-Mode), 0.4 Watt (Energy saving standby)
Heat Dissipation	4,423 BTU/hour (max)
Supply Voltage	AC 200 V - 240 V, 50 Hz - 60 Hz
Product dimensions	586 x 492 x 218 mm (Width x Depth x Height)
Product weight	24.4 kg
Noise Level	Normal:45 dB (A) - Economy:37 dB (A)
Supported Temperature	Storage -10° C - 60° C
Supported Humidity	Operation 20% - 80%, Storage 10% - 90%
Included Software	Epson Creative Projection, Epson Projector Config Tool, Epson Projector Content Manager, Epson Projector Management, Epson Projector Professional Tool
Options	Camera module, Ceiling mount, Wireless LAN unit
Room Type / Application	Boardroom, Large Meeting Room / Auditorium, Meeting room / Classroom, Projection Mapping, Rental / Staging, Signage / Retail, Visitor Attraction
Positioning	Ceiling Mounted, Desktop, Flying Frame
Colour	Black
OTHER	
Warranty	36 months Carry in Optional warranty extension available

EB-PU2220B

WHAT'S IN THE BOX

- Power cable
- Remote control incl. batteries
- Cable cover
- Lens connector cap
- Document Pack
- Information sheet
- Main unit
- Quick Start Guide

OPTIONAL ACCESSORIES

- Wireless LAN Adapter - ELPAP11 (2.4GHz & 5GHz)
V12H005A01
- Camera Unit - ELPEC01
V12HA46010
- Ceiling Mount - ELPMB68
V12H006AE0
- Extension Pole - ELPMB70 - For ELPMB68
V12H006AG0
- Truss Adaptor - ELPMB71 - For ELPMB68
V12H006AH0
- Stacking Frame - ELPMB59 - EB-PU2200 Series (EVO)
V12H996B59
- Stacking Frame - ELPMB84 - EB-PU2200 Series
V12H006AW0
- Portrait Adaptor - ELPMB78 - EB-PU Series
V12H006AQ0
- Tilt Adaptor - ELPMB81 - EB-PU Series
V12H006AT0

EB-PU2220B

OPTIONAL LENSES

Throw Ratio:

Lens Shift:

- | | | |
|---|---------------|-----------------|
| ● Lens - ELPLL08 - Long throw - EB-PU Series
V12H004L08 | 5.27 - 7.41:1 | V: ±60% H: ±18% |
| ● Lens - ELPLM10 - Mid throw 3 - EB-PU Series
V12H004M0A | 2.42 - 3.71:1 | V: ±60% H: ±18% |
| ● Lens - ELPLM11 - Mid throw 4 - EB-PU Series
V12H004M0B | 3.54 - 5.41:1 | V: ±60% H: ±18% |
| ● Lens - ELPLM15 - Mid throw - EB-PU Series
V12H004M0F | 1.57 - 2.56:1 | V: ±60% H: ±18% |
| ● Lens - ELPLU03S - Short throw off axis 1 - EB-PU Series
V12H004UA3 | 0.48 - 0.57:1 | V: ±24% H: ±10% |
| ● Lens - ELPLU04 - Short throw off axis 2 - EB-PU Series
V12H004U04 | 0.64 - 0.77:1 | V: ±60% H: ±18% |
| ● Lens - ELPLW06 - Wide zoom 2 - EB-PU Series
V12H004W06 | 1.19 - 1.62:1 | V: ±60% H: ±18% |
| ● Lens - ELPLW08 - Wide throw - EB-PU2000 Series
V12H004W08 | 0.86 - 1.2:1 | V: ±60% H: ±18% |
| ● Lens - ELPLX02S - UST - EB-PU2000 Series
V12H004X0B | 0.35:1 | V: +25% H: ±15% |

LOGISTICS INFORMATION

SKU	V11HA66840
EAN code	8715946703213
Country of Origin	China

* Warranty offers are not available for all countries. Please contact your local Epson representative.

For further information please contact your local Epson office or visit www.epson-europe.com

Austria 01 253 49 78 333 Belgium +32 (0)2 792 04 47 Czech 800/142 052 Denmark 44 50 85 85 Finland 0201 552 091 France 09 74 75 04 04

(Cost of local call, operator charges may apply) Germany +49 (0) 2159/92 79 500 Greece +30 211 198 62 12 Hungary 06800 147 83 Ireland 01 436 7742

Italy 02-660321 10 (0,12 /min) Luxembourg +352 27860692 Middle East +9714 8872172 Netherlands +31 (0)20 708 5099 Norway +47 67 11 37 00

Poland 0-0-800 4911299 (0,16 zł/min) Portugal 707 222 111 Russia (095) 777-03-55 Slovakia 0850 111 429 South Africa (+2711) 465-9621

Spain 93 582 15 00 Sweden 0771-400135 (Mobilsamtal – 0,99 kr/min, Lokala samtal – 0,30 kr/min, Utlandssamtal – 0,89 kr/min) Switzerland 022 592 7923

Turkey (0212) 3360303 United Kingdom 0871 222 6702

1. As of March 2023. Main unit including standard lens (ELPLM15). 20,000lm in accordance with ISO 21118.

Trademarks and registered trademarks are the property of Seiko Epson Corporation or their respective owners. Product information is subject to change without prior notice.

EPSON®